

CERTIFICATE OF COMPLIANCE

Certificate Number R39090
Report Reference R39090-20170313
Issue Date 2020-MARCH-12

Issued to: ATHMER OHG
Sophienhammer
59757 Arnsberg-Mueschede GERMANY

**This certificate confirms that
representative samples of**

ANCILLARY FIRE DOOR HARDWARE - BS 476: PART 22
SEE ADDEDNDUM PAGE

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety: SEE ADDENDUM PAGE

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R39090
Report Reference R39090-20170313
Issue Date 2020-MARCH-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Automatic Door Bottom Type Gasketing Models

Doppeldicht M12/35 1-seitig, NOR810, Schall-Ex L-14/35 EK, Schall-Ex Applic A (anod.silver), Schall-Ex Applic A (white), Schall-Ex Applic A (oak raw), Schall-Ex L15-FS, Schall-Ex L-15/30 WS, Schall-Ex Ultra OS, Schall-Ex L-15/30 OS, Schall-Ex XL-15/30 WS, Schall-Ex XL-15/30 OS, Schall-Ex Ultra HN einseitig / DDS 20 (Art. Nr. 1-489), Schall-Ex Ultra WS, Stadi L-24/20 WS (Art. Nr. 1-609), Stadi L-24/20 OS (Art. Nr. 1-605), Stadi L-24/20 TS (Art. Nr. 1-607), Schall-Ex L15/30 HN (Art. Nr. 1-499), Schall-Ex L15/30 (Art. Nr. 1-360), Schall-Ex L15/30 PIVOT, Stadi M-17/17 WS, Doppeldicht M12/35 2-seitig, Schall-Ex Duo L-15 WS, Schall-Ex Duo L-15/30 VS, Schall-Ex Duo L-15/31 OS, Schall-Ex Duo L-15/28 OS, Schall-Ex Duo L-15 QFS, Schall-Ex Duo L-15 QF, Schall-Ex Ultra WS, Schall-Ex Ultra OS, Stadi L-17/20 WS, Stadi L-20/20 WS, Stadi L-24/20 WS (Art. Nr. 1-938), Stadi L-24/20 OS (Art. Nr. 1-959), Stadi L-24/20 TS (Art. Nr. 1-960), Stadi FA-24/20 WS, Athmer Rainstop L-24/20 WS, Stadi MD-17/17 WS, Stadi LD-17/20 WS, Stadi LD-20/20 WS, Stadi LD-24/20 WS .

Standard(s) for Safety

Test Name	Standard/Paragraph	Representative Standard
Fire Endurance	UL 10C	UL 10B, CAN/ULC S104
Hose Stream	UL 10C	UL 10B, CAN/ULC S104



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

